

# Tor anti-climb paint

DM409

## intended uses

As a thick non-drying coating for parapets, downcomers, pipes etc as a deterrent to would-be intruders, burglars and vandals.

## product description

Lightly pigmented Petroleum Wax

## product information

|                                |  |
|--------------------------------|--|
| <b>Product reference</b>       | DM409                                    |
| <b>Volume solids</b>           | 100%                                     |
| <b>Typical thickness</b>       | 1000 microns                             |
| <b>Theoretical coverage</b>    | 1 square metre per litre                 |
| <b>Practical coverage</b>      | Reduce theoretical coverage by up to 20% |
| <b>Appearance/Colour range</b> | Black/ grey                              |
| <b>VOC content</b>             | 8 grams per litre of paint               |

## application details

|                              |   |
|------------------------------|---|
| <b>Mix ratio</b>             | N/A   |
| <b>Method of application</b> | Apply 1 coat by stiff nylon brush or lambswool mitt |
| <b>Thinner</b>               | Not required  |
| <b>Cleaner</b>               | Tor TH10 for cleaning equipment                     |
| <b>Pot Life</b>              | N/A   |

### Drying time

| Substrate Temperature | Touch Dry | Hard Dry | Overcoating Interval |         |
|-----------------------|-----------|----------|----------------------|---------|
|                       |           |          | Minimum              | Maximum |
| 20°C                  | -         | N/A      | -                    |         |

**Note:** Drying/curing times will be shortened by higher temperatures and lengthened by lower temperatures

## storage and handling

|                       |  |
|-----------------------|--|
| <b>Storage</b>        | In a safe place out of the reach of children |
| <b>Pack Size</b>      | 5 litres                                     |
| <b>Flash point</b>    | Above 55°C                                   |
| <b>Product weight</b> | 1.10 kilos/litre                             |
| <b>Shelf life</b>     | 5 years in unopened containers               |

## surface preparation

All surfaces to be coated must be clean, sound and dry. Porous surfaces should be sealed with 1 coat of Tor Stabilising Solution AK602.

Bare steel after cleaning to Swedish Standard ST2 should be given one coat of Tor QD Red Oxide Metal Primer AK618.

Plastic downcomers should be roughened by rubbing with medium grade abrasive paper.

## limitations

Only apply to areas above 6ft from ground level in order to avoid accidental contact.

Will attract a surface layer of dust which will not affect the material's performance.

## safety precautions

A copy of the appropriate Health & Safety Data Sheet should be consulted prior to using the product.

Minimum precautions for all paints:

1. Avoid skin and eye contact i.e. wear gloves, goggles, etc
2. Ensure good ventilation, mechanical if necessary.
3. Store and use away from heat and flame.
4. Do not eat or smoke in the vicinity of work.
5. Wash hands before eating.
6. Refer to supply container for additional warning labels.

## definitions

### **Tolerances**

All information quoted in this data sheet is subject to normal manufacturing tolerances.

### **Practical coverage**

Practical coverage can vary considerably depending on method of application, surface roughness, weather conditions and complexity of the structure.

### **Pot Life**

Applies only to two component products and refers to the time the mixture remains usable.

## disclaimer

The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Tor Coatings be liable for consequential or incidental damages.

This document will normally be updated at least every two years. It is the users responsibility to ensure that they have the current copy.

**Updated: March 2009**